

Welcome to Latex Processing Manufacturer for Cleanroom Materials & Medical Devices KOMEX CORPORATION

Heavy Duty Finger Cots - F500

Manufacturing Standard: ASTM D3772-15 (2021)

Product Code

Features F500

Made from natural rubber Latex, Least pre-powdered, White or Transparent Color,

Textured, Unrolled, Thicker thickness.

M. L or XL Available size, Medium, Large, X-Large.

Textured surface on tip for 25 to 30 mm long, ensuring easy & tightly gripping devices.

Application

General purpose for safety on human skin and protecting devices from contamination.


For use in handling rough surface devices, gardening, agricalural item processing, or handling fish.

For medical purose covering first aid bands over cuts on fingers.

Conforming (EU) 2017/745 MDR under CE registration no. DE/CA22/00176812



Mass & Dimensional Information;



| | | <u>Small</u> | <u>Medium</u> | <u>Large</u> | X-Large | XX-Large | Remarks |
|-----------------------------------|----|--------------|---------------|--------------|-------------|----------|------------|
| a. Average mass per piece | g | | 0.80 ± 0.05 | 0.88 ± 0.05 | 1.00 ± 0.05 | | |
| b. Width at mid & flat | mm | | 27 ± 2 | 29 ± 2 | 33 ± 2 | | |
| c. Length with rim (Rolled) | mm | | 70 ± 2 | 70 ± 2 | 70 ± 2 | | Adjustable |
| d. Rim thickness | mm | | 1 ± 0.2 | 1 ± 0.2 | 1 ± 0.2 | | Adjustable |
| e. Film thickness in double walls | mm | | 0.40± 0.04 | 0.40± 0.04 | 0.40± 0.04 | | Adjustable |
| f. Thickness at tip | mm | | > 0.40 | > 0.40 | > 0.40 | | Adjustable |

Length & Thickness are adjustable to meet customer's requirement

Physical Properties

| a. Tensile Strength | Мра | > 18 |
|---------------------|-----|--------|
| b Flongation | % | > 700% |

ESD Control

| Surface Resistivity | Ohms/cm2 | 10 F 9-11 |
|---------------------|----------|-----------|

Packaging Information

- a. 100 pcs in zipper pouch, 250 pouches in a shipping carton.
- b. 144 pcs (1 gross) in paper case, 100 cases in a shipping carton
- c. 5 gross (720 pcs) / Poly bag, 40 poly bags in a shipping carton
- d. 10 gross (1440 pcs) / Poly bag, 20 poly bags in a shipping carton.

Storage condition & Shelf Life

Storage indoor at dark place & lower than 25°C. Shelf life: 2 years from manufacturing date.

Test Report & Certification

- a. Safety Data Sheet
- b. ISO 9001
- c. CE registration no. DE/CA22/00176812


#Contact for further details : sales@komexcorp.com







KMX®



- Address: T-7110, 66, Chungmin-ro, Songpa-gu, Seoul, 05838 Republic of Korea(Garden 5,Life)

Factory (Binh Phuoc, Vietnam)

Address: Lot no. A 2.4, Chon Thanh 1 Industrial Zone, Thanh Tam Ward, Chon Thanh Town, Binh Phuoc Province, 833300 Vietnam

▼ Tel: 82-2-2202-1947 |

Email: kmxkwon@komexcorp.com